


## MS-9SH90-FWB


**Multi-Beam broadband Spherical Lens Antenna to support fixed wireless broadband LTE 40 and 42 bands: 9 independent high-frequency (2300MHz – 2400MHz & 3400MHz - 3600MHz) cross-polarized beams, with 0-15° tilt for each beam and 2X2 MIMO support per beam.**

- MS-9SH90-FWB (Non-RET Model)
- MS-9SH90-FWB-S (RET Model)




### PATTERN RESULTS:

**Horizontal Antenna Patterns (2.35GHz)**



**Vertical Antenna Patterns (2.35GHz)**



### TECHNICAL SPECIFICATIONS PER BEAM

Frequency	2300MHz -2400MHz & 3400MHz - 3600 MHz
Gain	25dBi
Return Loss	>15dB
Polarization	Dual Slant ±45°
Horizontal Coverage	120°
Horizontal Beamwidth (10dB level)	15° ± 1.5°
Vertical Beamwidth (10dB level)	14-16°
Beam Cross-over	7±1 dB typical
Total Number of Beams	9
Tilt Adjustment Per Beam	0° to 15°
First Sidelobe level	<-16dB
Front to Back Ratio	>28dB
Isolation Port to Port - Polarization	>28dB
Isolation Port to Port - Beam	>28dB
Power Rating	200W per port
Intermodulation	<-153dBc
Impedance	50 ohm
Connector Quantity and Type	18 x 4.3-10 DIN female

### MECHANICAL DATA

Dimensions (H x W x D)	Spherical Lens diameter: 90cm / 36inch  Antenna dimensions: 105.4 x 113.7 x 109.9 cm 41.5 x 44.8 x 43.3 inch
Antenna Weight	49.86 kg 109.9 lbs
Radome Material	Fiber Glass
Mounting	2 position pipe mount  Compatible pipe diameter: 6.1 – 11.4 cm 2.4 – 4.5 inch

### ENVIRONMENTAL RATINGS

Humidity	95% RH @ +30°C
Temperature	-40°C to +70°C
Wind load	754 N @ 151 km/hr 170 lbf @ 151 km/hr

### CONNECTOR LAYOUT:

